



UV TOP COAT – GUIDANCE NOTES AND INSTRUCTIONS

RoofSkin UV Top Coat is a solvent based, high performance two pack polyurethane flexible coating having good abrasion and chemical resistance. Ideal for floors and walls.

A Material Safety Data Sheet is available within Technical Data section of our website
www.RoofSkin.co.uk

BENEFITS

- Hard, tough and abrasion resistant,
- Good chemical resistance,
- Impervious finish ensures ease of cleaning
- Excellent adhesion to **RoofSkin**
- Excellent UV and heat stability.

TOOLS AND PROTECTIVE EQUIPMENT REQUIRED

- Wide Paint Brush OR Roller and Tray
- Wear gloves and protective clothing when using **RoofSkin UV Top Coat**.
- A suitable barrier cream is also recommended.
- In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
- After contact with skin, wash immediately with soap and water.

SURFACE PREPARATION

The efficiency of the **RoofSkin UV Top Coat** is dependant on the preparation of the substrate. Substrates should be free from all types of contamination i.e. dirt, grease, oils, fat and laitence.

MIXING AND APPLICATION

Add the contents of Part "B" to Part "A" and mix thoroughly. Failure to mix thoroughly could result in a poor or non-cure material. Apply immediately by brush or roller.

STORAGE

Store in sealed containers between 5°C and 35°C.

CLEANING

RoofSkin Tool Cleaner should be used for cleaning tools, etc.

WORKING TIME

Pot Life (at 20°C) 4 hours

Once both parts have been mixed

Application Temperature 5 - 30°C

Theoretical coverage:

10m² per kilogram (to give 50 microns DFT)

S.G. (Mixed) 1.20

Drying times

Touch dry: 4 hours. Hard: 8 hours

Overcoating times

Min 8 hours.

Max: 2 days

Service temperature -10°C to 100°C

HEALTH AND SAFETY

A Material Safety Data Sheet is available within Technical Data section of our website

www.RoofSkin.co.uk

For any questions or assistance please contact the ***RoofSkin*** team;

Tel: 01704 336826

Email: Technical@RoofSkin.co.uk

www.RoofSkin.co.uk

RoofSkin is a part of S.FLEX Polymer RoofingSystems, a trading division of PNR Global LTD.

Registered Office: Birkdale, Southport, PR8 4PW

Company Registration No: 07467064